

Nokia 7368 ISAM ONT G-010G-P

Residential ONT

The Nokia 7368 Intelligent Services Access Manager (ISAM) Optical Network Terminal (ONT) G-010G-P is the answer for home networking delivered by Gigabit Passive Optical Network (GPON). It is designed to connect individual users to the network for ultra-broadband services with gigabit speed. The Nokia 7368 ISAM ONT G-010G-P provides GPON interface to the subscriber and paves the way to deliver premium triple play services in a fiber to the home (FTTH) environment. The Nokia 7368 ISAM ONT G-010G-P is designed to take advantage of the Nokia award-winning management platforms, including the Nokia 5520 Access Management System (AMS) platform.

This residential ONT is designed to deliver Ethernet services to the subscriber through FTTH on one Gigabit Ethernet (GigE) port, which has the ability to burst up to a full gigabit dynamically. It is a temperature non-hardened ONT suitable for indoor deployments. Compliant with the standard ONT Management Control Interface (OMCI) definition, the G-010G-P ONT can be managed from a remote site using an AMS and can support the full range of fault, configuration, accounting, performance and security (FCAPS) functions.



Features

- Supports one GigE interface
- Wire speed data transfer for all packet sizes
- Per-subscriber, per-service bandwidth control
- Remotely managed by the Nokia 5520 AMS
- IP video with multistage Internet Group Management Protocol (IGMP) v2/v3 for channel change
- Supports received signal strength indication (RSSI) for lean operations and remote troubleshooting

Benefits

- Eco-sustainability in line with “green” tendencies: low power consumption
- IGMP snooping for monitoring the member joining-and-leaving activities at the Ethernet port and then selectively delivers the multicast streams
- Advanced dynamic bandwidth management allows prioritization per service and user with the ability to burst up to the full line rate. This guarantees very high quality of service and future security, and makes optimal use of electronics, fiber optics and distribution facilities

Technical specifications

Physical

- Height: 120mm (4.7in)
- Width: 90mm (3.5in)
- Depth: 33mm (1.3in)
- Weight: 0.12kg (0.26lb)
- Wall or desk mount

Operating environment

- Temperature: 0°C to 50°C (32°F to 122°F)
- Relative humidity: 5% to 95%

Power requirement

- Local powering with 12V input (feed uses external AC/DC adapter)
- Dying gasp support
- Power consumption: <4W

GPON uplink

- 1490nm wavelength downstream, 1310nm wavelength upstream
- 2.488Gb/s line rate downstream, 1.244Gb/s line rate upstream

- SC/APC optical connector
- Compliant with ITU-T G.984.2 Amd1, Class B+
 - +1dBm ~ +5dBm launch power, -28dBm sensitivity and -8dBm overload
- Compliant with ITU-T G.984.2 Amd1, Class C+ (optional)
 - +1dBm ~ +5dBm launch power, -30dBm sensitivity and -8dBm overload
- G.984.3-compliant dynamic bandwidth reporting ([DBR] by piggyback)
- G.984.3-compliant Advanced Encryption Standard (AES) in downstream
- G.984.3-compliant forward error correction (FEC) in both directions
- 802.1p fixed mapping to queues
 - Mapping of GPON Encapsulation Method (GEM) ports into a T-CONT
 - Remote software image download, activation and reboot

Ethernet interface

- IEEE 802.3-compliant 10/100/1000Base-T ports
- Medium dependent interface/medium dependent interface crossover (MDI/MDIX) automatic sense
- Data transferring at wire speed

Voice

- External integrated access device (IAD) is needed to delivery voice service on FTTH

IP video service

- Supports IGMPv2 and IGMPv3 snooping
- G.984.3-compliant multicast
- Uses a single GEM port-ID for all video traffic (as mandated by G.984.3)
- Supports multicast GEM port and incidental broadcast GEM port



LED

- Power
- Alarm
- Connection
- Ethernet

Safety and electromagnetic interference (EMI)

- Protection of over voltage/current

Regulatory compliance

- CE Mark
- RoHS 6
- CoC v5

Nokia is a registered trademark of Nokia Corporation. Other product and company names mentioned herein may be trademarks or trade names of their respective owners.

Nokia Oyj
Karaportti 3
FI-02610 Espoo
Finland
Tel. +358 (0) 10 44 88 000

Product code: PR1603018528EN